According to Regulation (EC) No. 1907/2006 (REACH)



Protactinium Generator R01192

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Protactinium Generator

Product No.: R01192 **SDS No.:** 906000

CAS No.:

EC No.:

Index No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Protactinium generator for use in educational science experiments.

Professional use only. Use only as described in the Protactinium Generator User Notes and Protactinium Generator Safe Handling

Instructions.

Uses advised against: Follow supplier's recommendations on correct use of the product.

1.3 Details of the supplier of the safety data sheet

Supplier: Philip Harris Manufacturing Ltd.

Unit 72, Gazelle Road Weston Industrial Estate Weston-super-Mare

BS24 9BJ

Telephone: +44 (0)1934 413 606

Fax: +44 (0)1934 626 421

E-mail: sdsinfo@philipharrismanufacturing.co.uk

1.4 Emergency telephone number

In case of emergency, call: +44 (0)1934 413 606

Monday - Thursday: 08:30 - 17:00 UK time

Friday: 08:30 - 13:00 UK time

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 1 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flam. Liq. 3; H226 Met. Corr. 1; H290 Acute Tox. 3; H301 Skin Corr. 1B; H314 Acute Tox. 4; H332 STOT SE 3; H335 Aquatic Chronic 3; H412

2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

R10

Toxic; T; R23/25

R33

Corrosive; C; R34 Irritant; Xi; R37

R52/53

2.2 Label elements

2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word: Danger.

Hazard Statement(s): H226: Flammable liquid and vapour.

H290: May be corrosive to metals.

H301: Toxic if swallowed.

H314: Causes severe skin burns and eye damage.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s): P210: Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P264: Wash thoroughly after handling.

P301 + P330 + P331: IF SWALLOWED: Rinse mouth, Do NOT

induce vomiting.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/ shower.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 2 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P405: Store locked up.

P501: Dispose of contents/container to hazardous waste collection point for disposal in accordance with local, regional, national or international regulations.

Supplemental Hazard information (EU):

None.

2.3 Other hazards

The product does not meet the criteria for PBT or vPvB substances.

The product contains uranium-238 and is a low level source of alpha and beta radiation.



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product consists of two immiscible liquids supplied in a fluorinated polyethylene (FEP).

Upper layer (ca. 10 mL): hexyl acetate with added dye.

Lower layer (ca. 30 mL): solution of uranyl nitrate in hydrochloric acid.

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification (Regulation (EC) No. 1272/2008 (CLP))	Classification (Directive 67/548/EEC)
Hydrochloric acid (36% w/w)	60-80	7647-01-0	231-595-7	017-002-01-X	Met. Corr. 1; H290 Skin Corr 1B; H314 STOT SE 3; H335	C; R34 Xi; R37
Hexyl acetate	10-15	142-92-7	205-572-7		Flam Liq. 3; H226	R10
Bis-(Nitrato-O) dioxo- uranium	3-5	10102-06-4	233-266-3		Acute Tox. 2; H300 Acute Tox. 2; H330 STOT RE 2; H373 Aquatic Chronic 2; H411	T+; R26/28 R33 N; R51/53

See Section 16 for full description of R phrases and H statements.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 3 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



SECTION 4: First Aid Measures

4.1 Description of first aid measures

INHALATION: Remove person to fresh air and keep comfortable for breathing. Keep warm and at rest. If

irritation persists or if you feel unwell, obtain immediate medical attention.

SKIN CONTACT: Take off immediately all contaminated clothing. Rinse skin with water/shower for at least

15 minutes. Obtain immediate medical attention. Contaminated clothing should be

washed before reuse.

EYE CONTACT: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Continue rinsing, making sure to rinse under eyelids. Obtain immediate

medical attention.

INGESTION: Do not induce vomiting. Provided the patient is conscious, rinse mouth out with water and

give 200-300 mL of water to drink. Never give anything by mouth to an unconscious

person. Obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes burns, blistering, redness and pain. Eye contact causes severe damage, watering, redness and pain. Inhalation of vapours may cause respiratory irritation, coughing and shortness of breath. Ingestion will cause burns to the mouth and digestive tract.

4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If breathing is laboured, oxygen should be administered by qualified personnel.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media

Suitable extinguishing media: Water spray, CO₂, sand, dry powder.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces. The vapours will spread along the ground and may be re-ignited by remote sources of ignition. Containers exposed to fire may burst due to a build-up of pressure.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen chloride, uranium oxides.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 4 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapours/spray. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate (See Section 8).

6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and clearing up

6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

6.3.2 For cleaning up

In case of spillage of entire contents: Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Transfer the contaminated absorbent material and damaged generator into a sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

In case of minor leak or seepage from container: Place leaking generator into sealed container for disposal. Wipe contaminated areas with damp tissues. Dispose of contaminated material as waste according to Section 13.

6.3.3 Other advice

Do not re-use a leaking protactinium generator.

6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof electrical and lighting equipment. Use only non-sparkling tools. Use only outdoors or in a well-ventilated area. Conduct experiments over a tray or similar to contain any spillage.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 5 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



DO NOT ATTEMPT TO OPEN THE GENERATOR. Do not squeeze the generator. Do not remove the clear protective sleeve from the generator. Hold by the ends using thumb and forefinger, and apply moderate pressure only. Do not use the generator at high room temperatures. To minimise internal vapour pressure on hot days, cool in refrigerator before use. Restore the generator to an upright position (cap uppermost) following completion of experiment. Check the protactinium generator for damage or leaks before use. Dispose of a damaged or leaking generator as described in Section 13.

Do not breathe vapours. Do not allow contents to come into contact with skin, eyes or clothing. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight. Store only in original container. Store the generator in the external container provided when not in use. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

Keep away from: oxidising agents, strong alkalis.

7.3 Specific end use(s)

Protactinium generator for use in educational science experiments. Professional use only. Use only as described in the Protactinium Generator User Notes and Protactinium Generator Safe Handling Instructions. Further information on handling and storage can be found in CLEAPSS bulletin L93 'Managing Ionising Radiations and Radioactive Substances in Schools and Colleges' available at http://www.cleapss.org.uk/download/L93.pdf

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Workplace exposure limits

Source: EH40/2005, 2nd Ed., 2011.

Substance	CAS No.	LTEL (8 hr TWA)		STEL (15 min)		Comments
Substance		ppm	mg/m³	ppm	mg/m³	Comments
Hydrogen chloride (gas and aerosol mists)	7647-01-0	1	2	5	8	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation to ensure that occupational exposure limits are not exceeded. The protactinium generator should not be opened if used correctly, in which case there should be no release of vapours.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 6 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



8.2.2 Personal protection

Eye protection: Goggles or safety glasses with side shields giving complete

protection to eyes (EN 166).

Skin protection:

Hand protection: Chemical-resistant gloves conforming (EN 374). Nitrile rubber

gloves are recommended for normal use. Butyl rubber gloves are recommended if the contents of the generator are released. Contact glove supplier to confirm suitable glove material, thickness and

breakthrough times.

Other: Long sleeve protective clothing.

Respiratory protection: Not normally required. If contents of the generator are released and

airborne levels below the exposure limits cannot be maintained, wear a positive pressure air-purifying respirator (EN 140) with a

Type E filter or better suitable for acidic gases. (EN 14387).

Thermal hazards: Not applicable.

8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: 2 immiscible liquids: dark yellow upper layer, pale yellow lower

layer.

Odour: Pungent.

Odour threshold: Not available.

pH: < 7

Melting/freezing point: Upper layer: -80°C

Lower layer: ca. -30°C

Initial boiling point and boiling range: Upper layer: 171°C

Lower layer: ca. 100°C

Flash point: Upper layer: 45-58°C

Evaporation rate:

Flammability (solid; gas):

Upper/lower flammability or explosive limits:

Vapour pressure:

Not available.

Not available.

Not available.

Relative density: Upper layer: 0.88 (20°C)

Lower layer: ca. 1 (Water = 1)

Solubility(ies): Upper layer: immiscible in water.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 7 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



Lower layer: miscible in water.

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Not available.

Not available.

Not available.

Viscosity:

Not available.

Explosive properties: Not explosive. Vapour may form explosive mixture in air.

Oxidising properties: Not oxidising.

9.2 Other information

None known.

SECTION 10: Stability and Reactivity

10.1 Reactivity Reacts with oxidising agents.
10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No hazardous reactions expected during normal use.

10.4 Conditions to avoid Keep away from sources of ignition, hot surfaces, direct sunlight.

Keep away from incompatible materials.

10.5 Incompatible materials Oxidising agents. Strong alkalis.

10.6 Hazardous decomposition products Combustion may liberate toxic fumes: Carbon monoxide, carbon

dioxide, nitrogen oxides, hydrogen chloride, uranium oxides.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity Toxic if swallowed. Harmful if inhaled.

Skin corrosion/irritationCauses severe skin burns.

Serious eye damage/irritation Causes serious eye damage.

Skin sensitisation Not classified. The product does not contain substances classified

as skin sensitisers above the classification thresholds.

Respiratory sensitisation Not classified. The product does not contain substances classified

as respiratory sensitisers above the classification thresholds.

Germ cell mutagenicity

Not classified. The product does not contain substances classified

as mutagenic above the classification thresholds.

Carcinogenicity Not classified. The product does not contain substances classified

as carcinogenic above the classification thresholds.

Reproductive toxicity

Not classified. The product does not contain substances classified

as toxic to reproduction above the classification thresholds.

According to Regulation (EC) No. 1907/2006 (REACH)



Specific Target Organ Toxicity –

single exposure

May cause respiratory irritation.

Specific Target Organ Toxicity -

repeated exposure

Not classified. The product does not contain substances classified for specific target organ toxicity following repeated exposure above

the classification thresholds.

Aspiration hazardBased on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause respiratory irritation.

Skin contactCauses skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Toxic if swallowed. Ingestion may cause burns to the mouth and

digestive tract.

Symptoms related to the physical, chemical and Skin contact causes burns, blistering, redness and pain. Eye contact

toxicological characteristics

causes severe damage, watering, redness and pain. Eye contact causes severe damage, watering, redness and pain. Inhalation of vapours may cause respiratory irritation, coughing and shortness of breath. Ingestion will cause burns to the mouth and digestive tract.

Mixture versus substance Information No data available.

Other information None.

SECTION 12: Ecological Information

12.1 Toxicity Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT and vPvB The product does not contain substances assessed to be PBT or

assessment vPvB.

12.6 Other adverse effects None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 9 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



SECTION 14: Transport Information

ADR		
14.1	UN Number	2920
14.2	UN Proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains
	erre reper emphg	hydrochloric acid, hexyl acetate), Radioactive material, excepted
440		package - limited quantity of material
14.3	Transport hazard class(es)	8
14.4 14.5	Packing group Environmental hazards	II No
14.5 14.6	Special precautions for the user	No Read SDS and supplier instructions on correct use of the product.
14.0	Special precautions for the user	Read 3D3 and supplier instructions on correct use of the product.
ADN		
14.1	UN Number	2920
14.2	UN Proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains hydrochloric acid, hexyl acetate), Radioactive material, excepted
		package - limited quantity of material
14.3	Transport hazard class(es)	8
14.4	Packing group	
14.5	Environmental hazards	No
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
RID		
14.1	UN Number	2920
14.2	UN Proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains
		hydrochloric acid, hexyl acetate), Radioactive material, excepted package - limited quantity of material
14.3	Transport hazard class(es)	8
14.4	Packing group	
14.5	Environmental hazards	No
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IATA/I	CAO	
14.1	UN Number	2920
14.2	UN Proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains hydrochloric acid, hexyl acetate), Radioactive material, excepted
		package - limited quantity of material
14.3	Transport hazard class(es)	8
14.4	Packing group	II .
14.5	Environmental hazards	No
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IMDG		
14.1	UN Number	2920

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 10 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



14.2	UN Proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains hydrochloric acid, hexyl acetate), Radioactive material, excepted package - limited quantity of material
14.3	Transport hazard class(es)	8
14.4	Packing group	II
14.5	Environmental hazards	No
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	The product is not intended to be transported in bulk.

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive 67/548/EEC & Directive 1999/45/EC.

15.2 Chemical Safety Assessment

A chemical safety assessment is not required and has not been carried out.

SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s):	H226: Flammable liquid and vapour.

H290: May be corrosive to metals.

H300: Fatal if swallowed. H301: Toxic if swallowed.

H314: Causes severe skin burns and eye damage.

H330: Fatal if inhaled. H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or

repeated exposure.

H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Supplemental Hazard

information (EU):

None.

Risk phrase(s): R10: Flammable.

R23/25: Toxic by inhalation and if swallowed. R26/28: Very toxic by inhalation and if swallowed.

R33: Danger of cumulative effects.

R34: Causes burns.

R51/53: Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 11 of 12

According to Regulation (EC) No. 1907/2006 (REACH)



Abbreviations:

CAS: Chemical Abstracts Service;

EINECS: European Inventory of Existing Commercial Chemical Substances

 EC_{50} : Effective Concentration 50% EL_{50} : Effective Loading rate 50% IC_{50} : Inhibitory Concentration 50% LC_{50} : Lethal Concentration 50%

LD₅₀: Lethal Dose 50%

LL₅₀: Lethal Loading rate 50%
 LCLo: Lowest lethal concentration
 LOEL: Lowest Observed Effect Level
 NOEL: No Observed Effect Level

PBT: Persistent, Bioaccumulative and Toxic. vPvB: Very Persistent and Very Bioaccumulative.

References:

Supplier's Safety Data Sheets for ingredients ECHA disseminated REACH dossiers ECHA Classification & Labelling Inventory

Approved Classification and Labelling Guide (Sixth edition)

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP)

Regulation (EC) No. 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP)

Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

Version history:

SDS Number: 906000 **Version**: 1.0

Issue date: 20/12/2013

Previous Version:

Issue date of previous version:

Sections changed from previous version:

 Version: 1.0
 Protactinium Generator
 SDS No.: 906000

 Date: 20/12/2013
 R01192
 Page 12 of 12