

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU AP FB 35ML*10 L390
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Fax: 0049-(0)7223-284-245

GB

www.uhu.com 1/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

| · Dangerous components: | | | |
|---|---|-----------|--|
| CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX | methyl acetate SE 3, H336, EUH066 | 50-100% | |
| CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43 | ethanol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50% | 2.5-10% | |
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX | Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | ≥2.5-<10% | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

OD

www.uhu.com 2/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

(Contd. on page 4)

GB

www.uhu.com 3/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

| 8.1 Contro | ol parameters | | |
|-------------|--|------------------------|--|
| Ingredien | ts with limit values that require monitori | ng at the workplace: | |
| | ethyl acetate | | |
| | rt-term value: 770 mg/m³, 250 ppm | | |
| | g-term value: 616 mg/m³, 200 ppm | | |
| 64-17-5 et | | | |
| | g-term value: 1920 mg/m³, 1000 ppm | | |
| 67-64-1 A | | | |
| | rt-term value: 3620 mg/m³, 1500 ppm g-term value: 1210 mg/m³, 500 ppm | | |
| | | | |
| DNELs | othyd godfafa | | |
| Oral | ethyl acetate Consumer, oral, longterm exposition | 21.5 mg/kg bw/day | |
| Dermal | Worker, dermal, longterm exposition | 43 mg/kg bw/day | |
| Demiai | Consumer, dermal, shortterm exposition | 203 mg/kg bw/day | |
| | Consumer, dermal, longterm exposition | 21.5 mg/kg bw/day | |
| labalativa | Worker, inhalative, shortterm exposition | 3777 mg/m³ | |
| IIIIIaiauve | Worker, inhalative, shortterm exposition | 300 mg/m ³ | |
| | Consumer DNEL, acute inhalation | 3777 mg/m³ | |
| | • | 64 mg/m³ | |
| 64-17-5 et | • | 0+ mg/m | |
| Oral | Consumer, oral, longterm exposition | 87 mg/kg bw/day | |
| Dermal | Worker, dermal, longterm exposition | 343 mg/kg bw/day (rat) | |
| | Consumer, dermal, longterm exposition | 206 mg/kg bw/day | |
| Inhalative | Worker, inhalative, shortterm exposition | 1900 mg/m³ (rat) | |
| | Worker, inhalative, longterm exposition | 950 mg/m³ (rat) | |
| | Consumer DNEL, acute inhalation | 950 mg/m³ (rat) | |
| | • | 114 mg/m³ | |
| 67-64-1 A | | 3 | |
| Oral | Consumer, oral, longterm exposition | 62 mg/kg bw/day | |
| Dermal | Worker, dermal, longterm exposition | 186 mg/kg bw/day | |
| | Consumer, dermal, longterm exposition | 62 mg/kg bw/day | |
| | Worker, inhalative, shortterm exposition | 2420 mg/m³ | |
| | Worker, inhalative, longterm exposition | 1210 mg/m³ | |
| | Consumer, inhalative, longterm exposition | 200 mg/m³ | |

www.uhu.com 4/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

| | (Contd. of page |
|--------------------------|----------------------------|
| PNECs | |
| 79-20-9 methyl acetate | |
| Oral Secondary Poisoning | 20.4 mg/kg |
| Fresh water | 0.12 mg/l |
| Fresh water sediment | 0.128 mg/kg dry weight |
| Marine water | 0.012 mg/l |
| Marine sediment | 0.013 mg/kg dry weight |
| Soil | 0.0416 mg/kg |
| Sewage treatment plant | 600 mg/l |
| 64-17-5 ethanol | |
| Fresh water | 0.96 mg/l |
| Fresh water sediment | 3.6 mg/kg dry weight (rat) |
| Marine water | 0.79 mg/l |
| Marine sediment | 2.9 mg/kg dry weight (rat) |
| Soil | 0.63 mg/kg |
| Sewage treatment plant | 580 mg/l (rat) |
| Sporadic release | 2.75 mg/l (rat) |
| 67-64-1 Acetone | |
| Fresh water | 10.6 mg/l |
| Fresh water sediment | 30.4 mg/kg dry weight |
| Marine water | 1.06 mg/l |
| Marine sediment | 3.04 mg/kg dry weight |
| Soil | 29.5 mg/kg |
| Sewage treatment plant | 100 mg/l |
| Sporadic release | 21 mg/l |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

(Contd. on page 6)

GB

www.uhu.com 5/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 18 (replaces version 17) Revision: 01.08.2024 Printing date 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 5)

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C · Flammability Highly flammable.

· Lower and upper explosion limit

3.1 Vol % · Lower: 16 Vol % · Upper: -13 °C · Flash point: 425 °C · Auto-ignition temperature:

Not determined. Decomposition temperature: Not determined.

· Viscosity:

· Kinematic viscosity Not determined. Dynamic at 20 °C: 4400 mPas

· water:

· Solubility

· Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 220 hPa Vapour pressure at 50 °C: 800 hPa

Density and/or relative density Density at 20 °C:

0.987 g/cm³ · Relative density Not determined. Not determined. · Vapour density

All relevant physical data were determined for the · 9.2 Other information

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

Not miscible or difficult to mix.

(Contd. on page 7)

6/12 www.uhu.com



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 6)

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 65.8 %
 Water: 0.4 %
 VOC (EC) 65.79 %
 Solids content: 33.8 %

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Void

· Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

www.uhu.com 7/12

GB -



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 · | · LD/LC50 values relevant for classification: | | | |
|-------------|---|---------------------|--|--|
| 79-20-9 m | 79-20-9 methyl acetate | | | |
| Oral | LD50 | 3705 mg/kg (rabbit) | | |
| 64-17-5 et | 64-17-5 ethanol | | | |
| Oral | LD50 | 10470 mg/kg (rat) | | |
| Dermal | LD50 | >2000 mg/kg (rat) | | |
| Inhalative | LC50/4 h | 120 mg/l (rat) | | |
| 67-64-1 A | 67-64-1 Acetone | | | |
| Oral | LD50 | 5800 mg/kg (rat) | | |
| Dermal | LD50 | >15800 mg/kg (rat) | | |
| Inhalative | LC50/4 h | 76 mg/l (rat) | | |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 9)

- GB

www.uhu.com 8/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 8)

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR/ADN



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR/ADN, IMDG, IATA III

(Contd. on page 10)

GB

www.uhu.com 9/12



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

| | (Contd. of page |
|--|--|
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): EMS Number: Stowage Category | F-E,S-D A |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| Transport/Additional information: Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml |
| Transport category Tunnel restriction code | 3 E |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml |
| Remarks: | For substances with class 3 according to IMDG Code chapter 2.3.2.2 packing group is classifie in packing group III, as viscosity is in accordanc with requirements (flow time t > 100s). |
| UN "Model Regulation": | UN 1133 ADHESIVES, 3, III |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 Acetone

Listed

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 11)

GE

www.uhu.com 10/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.08.2024 Version number 18 (replaces version 17) Revision: 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 10)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 Acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 Acetone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 Acetone

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

| · Classification according to Regulation (EC) No 1272/2008 | | | |
|--|--|--|--|
| Flammable liquids | Bridging principles | | |
| | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. | | |

· Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 29.07.2024
Version number of previous version: 17

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

- GB

www.uhu.com 11/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 18 (replaces version 17) Revision: 01.08.2024 Printing date 01.08.2024

Trade name: UHU AP FB 35ML*10 L390

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

12/12 www.uhu.com