



Available as Foot Operated, Hand Operated or Hand and Foot Operated.

Fire Retardant Sackholder - Fixed Body SKU - ENF48083946 Vendor REF - RFG/1FP WHITE Fire Retardant Sackholder - Removable Body SKU - ENF48323197 Vendor REF - RFG/1RB WHITE



Visual Specification Metal Sackholder

| RFG-Metal range | 70 Litre Removable Body |
|---|---|
| Wybone Code | RFG/1 |
| Pedal Operated Metal Sackholder | 70 Litre |
| Construction | |
| Metal sackholders consist of powder co | oated, galvanised steel lid, frame, feet & fixings and a plastisol (plastic coated steel) body |
| Body | British Steel HP200 Plastisol body. Hot dipped galvanised with decorative protective finish, giving outstanding corrosion resistance. Conforms to Class 'O' Building Regulations, BS 476 Part 7 Spread of Flame and BS 476 Part 6 Fire Propagation. British Board of Agrement approved. Meets the requirements of HTM 05:03 - Fire Code - Fire Safety in the NHS. |
| Lid | Lightweight 0.9mm hot dipped coated galvanised steel to BSEN10327 grade DX51D + Z275 offering outstanding corrosion resistance |
| Frame | Easy clean sack retaining frame manufactured in 1.2mm hot dipped coated galvanised steel to BSEN10327 grade DX51 + Z275 offering outstanding corrosion resistance |
| Rod | Electrogalvanised 8mm diameter mild steel push rod |
| Castors | Integrated 50mm non-marking nylon fixed castors to rear of unit to aid manoeuverability and prevent damage/marking to walls |
| Pedal | 15mm -16mm diameter electrogalvanised tubular pedal with powder coating for corrosion protection. |
| Foot unit | Sturdy foot unit manufactured in 1.5mm hot dipped coated galvanised steel to BSEN10327 grade DX51 + Z275 offering outstanding corrosion resistance with rubber feet to bottom to prevent marking on floors |
| Surface finish | |
| | and powder coated with tough oven cured epoxy powder, with anti-bacterial Silver lon technology and containing no volitile organic compounds |
| Lids colour coded to comply with HTM (| 07:01 Safe Management of Healthcare Waste to aid the correct segregation of waste streams |
| Product Dimensions | |
| Width (in mm) | 426 |
| Depth (in mm) | 375 |
| Height (in mm) | 800 |
| Additional Options | |
| Hands free frame (add //HF to end of Wybone code) | Hands free frame- prevents the lid being opened by hand to stop the spread of infection - can only be opened via the foot pedal |
| Removable Body (add /RB to end of Wybone code) | A removable body gives easy access to the whole bin easier to clean |
| Gas strut for soft closing lid (add /S/LID to end of Wybone code) | A gas strut is fitted to the back of the lid which allows the lid to close gently, reducing noise |
| Warranty | - |

the UK. Their integrity and construction ensures that our products will provide many years of trouble free operation. In the unlikely event that problems occur, our products are covered by:

1 year parts and labour.

10 years anti-perforation warranty.