

DataSheet

Market-leading Commander® has something new to offer – CommanderEDGE. BS EN3 Kitemark approved across the range, this range has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO₂ and Powder models and offers solutions for almost all situations. The internationally-recognised BS Kitemark is assurance of dependable design and manufacture.

FOAM FIRE EXTINGUISHERS

Foam is always an excellent choice for Class A and B fires. The standard 6 and 9 litre models have passed the 35kVa Dielectric test and comply fully with BS EN3-7: 2004 Clause 9 - Dielectric test for water-based extinguishers. The newly-developed 6 litre EnviroFoam is a true market leader with an environmentally-friendly foam and boasting a high performance 27A 183B fire rating.

Technical Specification	FS2E	FS6E	FS6ECO	FS9E
Capacity	2 litre	6 litre	6 litre	9 litre
Fire Rating	5A 34B	13A 144B	27A 183B	21A 183B
Extinguishing Medium	AFF Foam	AFF Foam	AFF Foam	AFF Foam
Working Pressure	14 bar	14 bar	14 bar	14 bar
Temperature Range	+5°-+60°C	+5°-+60°C	+5°-+60°C	+5°-+60°C
Cylinder Material	Steel	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen



COMMANDEREDGE

PRODUCT CODE

FS2E | FS6E | FS6ECO | FS9E

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FS2E: 380 x 125 x 120

FS6E: 550 x 310 x 165

FS6ECO: 550 x 310 x 165

FS9E: 620 x 330 x 185

WEIGHT

FS2E: 4.5kg

FS6E: 9.6kg

FS6ECO: 9.6kg

FS9E: 14.2kg

- Kitemarked to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Plastic base skirt for protection
- Polyethylene internal lining
- 35kVa Dielectric test certified on 6 and 9ltr

