

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1

Revision Date: 14.05.2003

Smart Putty - Dilatant Compound

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone compound

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Quartz	14808-60-7	238-878-4	17.0	Xn	R48/20 R68/20
Glycerine	56-81-5	200-289-5	1.0		
Decamethylcyclopentasiloxan e	541-02-6	208-764-9	1.0		

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

4. FIRST AID MEASURES

On contact with eyes : No first aid should be needed.

On skin contact : No first aid should be needed.

If inhaled : No first aid should be needed.

On ingestion : No first aid should be needed.

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1 Revision Date: 14.05.2003

DILATANT COMPOUND

5. FIRE FIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire

exposed containers.

Unsuitable extinguishing

media

None known.

Hazards during fire fighting: None known.

Special protective

equipment/procedures

A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate

the area according to your local emergency plan.

Hazardous Combustion

Products

Silica. Carbon oxides and traces of incompletely burned carbon compounds.

Formaldehyde. Quartz. Metal products.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear proper protective equipment.

Precautions to protect the

environment

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or

other appropriate barriers.

Methods for cleaning up : Determine the need to evacuate or isolate the area according to your local emergency

plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product

produces an extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling : Avoid eye contact. General ventilation is recommended.

Advice on storage : Do not store with oxidizing agents.

Specific uses : Refer to technical data sheet available on request.

Unsuitable packaging

materials

None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation: Refer to Section 7

Exposure controls for hazardous components

Name CAS-No. Exposure Limits

2 of 6

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1 Revision Date: 14.05.2003

DILATANT COMPOUND

Quartz 14808-60-7 0.3 mg/m3 TWA Respirable dust

Glycerine 56-81-5 10 mg/m3 TWA

Decamethylcyclopentasiloxane 541-02-6 10 ppm TWA Dow Corning recommendation.

Personal protection equipment

Respiratory protection: Suitable respiratory protection should be worn if the product is used in large quantities,

confined spaces or in other circumstances where the OEL may be approached or

exceeded.

Hand protection : Gloves are not normally required.

Eye protection : Safety glasses should be worn.

Skin protection : Protective equipment is not normally necessary.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Environmental exposure

controls

Refer to section 6 and 12.

Additional information : These precautions are for room temperature handling. Use at elevated temperature or

aerosol/spray applications may require added precautions. For further information regarding the use of silicones in consumer aerosol applications, please refer to the guidance document regarding the use of silicone-based materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or

contact the Dow Corning customer service group.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: Viscous Liquid Colour: Pink Odour: None

Other data

Boiling point/range : > 35C/95F

Flash point : > 93.8 °C (Closed Cup)

Explosive properties : No

Specific Gravity : 1.14

Viscosity : 10000000 cSt at 25°C.

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1 Revision Date: 14.05.2003

DILATANT COMPOUND

10. STABILITY AND REACTIVITY

Stability : Stable under normal usage conditions.

Conditions to avoid : None established.

Materials to avoid : Can react with strong oxidising agents.

Hazardous decomposition

products

See section 11.

11. TOXICOLOGICAL INFORMATION

On contact with eyes : May cause temporary discomfort.

On skin contact : No adverse effects are normally expected.

If inhaled : No adverse effects are normally expected.

On ingestion : No adverse effects are normally expected.

Other Health Hazard

Information

Product may emit formaldehyde vapours at temperatures above 150°C in the presence of

air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory system at breathing concentration less than one part per million (1 ppm).

Human health hazards associated with quartz (silica, crystalline respirable dust) and other fibrogenic dusts arise following inhalational exposure to respirable particles. Quartz in the present formulation (uncured or cured) is not available in a respirable form.

- ¹ Based on product test data.
- Based on test data from similar products.
- This information is based either on test data, extrapolation from tests on similar materials, review of component data, or a combination of these sources.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

Ecotoxicity effects

No adverse effects on aquatic organisms.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

Additional environmental information

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1 Revision Date: 14.05.2003

DILATANT COMPOUND

Additional environmental information on the silicone component is available on request.

13. DISPOSAL CONSIDERATIONS

Product disposal : Dispose of in accordance with local regulations.

Packaging disposal : Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Labelling according to EEC Directive

S-phrases : S51 Use only in well-ventilated areas.

National legislation / regulations

Ozone depleting

chemicals

No ozone depleting chemicals are present or used in manufacture.

Status

EINECS : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.1 Revision Date: 14.05.2003

DILATANT COMPOUND

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation., **R68/20** Harmful: possible risk of irreversible effects through inhalation.