



Technical Data Sheet



Technical Data Sheet
Ref: PR22000
Issued: 20.07.2017
Number of pages: 2

Pritt Rainbow Sticks

Solvent-free glue stick (10g, 20g)

CHARACTERISTICS

- Water-based glue stick for crafting and hobby
- Permanent coloured glue sticks: blue, green, yellow, red
- CE conform according to EN 71
- Solvent-free
- Acid-free
- 90% renewable ingredients (incl. water)
- Washable at 20°C
- Easy application
- High initial tack
- High efficiency
- Suitable for paper, cardboard, felt, cork and lightweight craft materials

APPLICATION FIELD

Glue stick adhesive for home, school and office. Ideal for crafting and hobby.

INSTRUCTIONS FOR USE

Pretreatment

Not necessary. In general, surfaces have to be clean, dry and free of dust and grease.



Application

Apply the adhesive two or three times on the surface and join the bonding parts together.
Close the cap properly after use to avoid drying out of the glue mass.
Correction of the bonding parts is possible within a short time after bonding.
Close cap tightly after use!

TECHNICAL DATA

Composition	Polyglycoside ether, polysaccharides, soap and water
pH	10.0-10.2
Open time*	up to 210 sec
Setting time*	60 - 90 sec
color	permanent colored: blue, green, yellow, red
Shelf Life	24 months at 20°C

*) parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

LIMITATIONS

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Limited

Road 5, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QY
Phone: +44 (0) 1606 593 933
Internet: www.henkel.co.uk
e.mail: technical.services@henkel.co.uk