

Hanna Instruments S.R.L.

HI3895K-0 - Potassium Reagent

Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 1 / 10 ΕN

Safety data sheet according to Regulation (EC) No. 1907/2006

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code. HI3895K-0

Product name. Potassium Reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Determination of Potassium in Soil (Extract) Samples.

1.3. Details of the supplier of the safety data sheet.

Name. Hanna Instruments S.R.L.

Full address. str. Hanna Nr 1
District and Country. 457260 loc. Nusfalau

457260 loc. Nusfalau (Salaj)

Romania Tel. (+40) 260607700

Fax. (+40) 260607700

e-mail address of the competent person.

responsible for the Safety Data Sheet. msds@hanna.ro

1.4. Emergency telephone number.

For urgent inquiries refer to. **Emergency Number - International: +(1)-703-527-3887 - UK, London:**

+(44)-870-8200418 - CHEMTREC 24 hours/365 days

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Harmful if swallowed.
Serious eye damage, category 1 H318 Causes serious eye damage.
Skin irritation, category 2 H315 Causes skin irritation.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H302 Harmful if swallowed.
H318 Causes serious eye damage.
H315 Causes skin irritation.

Precautionary statements:

P280 Wear protective gloves / eye protection / face protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

@EPY 9.2.8 - SDS 1003



Revision nr 1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 2/10

ΕN

SECTION 2. Hazards identification.

P310 Immediately call a POISON CENTER or doctor.

Contains: **EDTA TETRASODIUM SALT**

SODIUM TETRAPHENYLBORATE

LITHIUM HYDROXIDE

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. x = Conc. %. Classification 1272/2008 (CLP).

EDTA TETRASODIUM SALT

CAS. 194491-31-1 $50 \le x < 100$

Acute Tox. 4 H302, Eye Dam. 1 H318 200-573-9

EC. INDEX. 607-428-00-2

SODIUM TETRAPHENYLBORATE

Acute Tox. 3 H301 CAS. 143-66-8 1 ≤ x < 5

FC 205-605-5

INDEX.

LITHIUM HYDROXIDE

Acute Tox. 3 H301, Skin Corr. 1A H314 CAS. 1310-66-3 $1 \le x < 3$

EC. 215-183-4

INDEX.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

SODIUM TETRAPHENYLBORATE

Muscular weakness. The following applies to boron compounds in general: resorption is followed by nausea and vomiting, agitation, spasms, CNS disorders, cardiovascular disorders.

LITHIUM HYDROXIDE

Irritation and corrosion, Cough, Shortness of breath, Risk of blindness! The following applies to lithium compounds in general: when handled or used inappropriately, the absorption of large quantities is followed by CNS disorders, agitation, spasms, ataxia (impaired locomotor coordination) due to disturbed electrolyte balance.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

@EPY 9.2.8 - SDS 1003



Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 3 / 10

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product and place it in containers for recovery or disposal. If the product is flammable, use explosion-proof equipment. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.



Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 4 / 10

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

			EDTA TET	RASODIUM SA	ALT			
Predicted no-effect cor	ncentration	- PNEC.						
Normal value in fresh water						2,2	mg/l	
Normal value in marine water						0,22	mg/l	
Normal value for water, intermittent release						1,2	mg/l	
Normal value of STP microorganisms						43	mg/l	
Normal value for the terrestrial compartment						0,72	mg/kg/	
Health - Derived no-eff	ect level - D	ONEL / DMEL					d	
	Effects on consumers.			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Inhalation.							1,5 mg/m3	VND

			LITHIUN	I HYDROXIDE				
redicted no-effect cor	ncentration	- PNEC.						
Normal value in fresh	n water					2,3	mg/l	
Normal value in marine water					0,23	mg/l		
Normal value for fresh water sediment					9	mg/kg/		
Normal value for marine water sediment					0,9	dng/kg/		
Normal value for water, intermittent release						0,344	r hg/l	
Normal value of STP microorganisms						79,2	mg/l	
Normal value for the terrestrial compartment					0,45	mg/kg/		
ealth - Derived no-eff	ect level - D	ONEL / DMEL					d	
	Effects on consumers.			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Inhalation.					VND	30 mg/m3	VND	10 mg/m3
Skin.					VND	100 mg/kg bw/d	VND	41,35 mg/kg
								bw/d

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Use a type P filtering facemask (see standard EN 149) or equivalent device, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 5 / 10

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

solid powder Appearance Colour white odourless Odour Odour threshold. Not available. 11.5 - 11.8, 10 g/L Melting point / freezing point. Not available. Initial boiling point. Not applicable. Boiling range. Not available. Flash point. Not applicable. Evaporation rate Not available. Not available Flammability (solid, gas) Lower inflammability limit. Not available. Not available. Upper inflammability limit. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 2.000

Solubility soluble in water
Partition coefficient: n-octanol/water Not available.
Auto-ignition temperature. Not available.
Decomposition temperature. Not available.
Viscosity Not available.
Explosive properties Not available.
Oxidising properties Not available.

9.2. Other information.

 Molecular weight.
 372,828

 Total solids (250°C / 482°F)
 100,00 %

 VOC (Directive 2010/75/EC):
 0

 VOC (volatile carbon):
 0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The powders are potentially explosive when mixed with air.

LITHIUM HYDROXIDE

Violent reactions possible with: acids.

10.4. Conditions to avoid.

Avoid environmental dust build-up.

10.5. Incompatible materials.

LITHIUM HYDROXIDE Aluminium, Lead, Zinc, Tin.

10.6. Hazardous decomposition products.

Information not available.





Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 6 / 10

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

LITHIUM HYDROXIDE

Acute oral toxicity, absorption, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach - Acute inhalation toxicity, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Inhalation may lead to the formation of oedemas in the respiratory tract - Skin irritation, tissue damage, Causes severe burns - Eye irritation, Causes serious eye.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component). LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).

LD50 (Oral) of the mixture: 13390,003 mg/kg

LD50 (Dermal) of the mixture: Not classified (no significant component).

EDTA TETRASODIUM SALT

LD50 (Oral). 630 mg/kg Rat

SODIUM TETRAPHENYLBORATE

LD50 (Oral). 288 mg/kg Rat

LITHIUM HYDROXIDE

LD50 (Oral). 210 mg/kg Rat LC50 (Inhalation). 210 mg/k/4h Rat

SKIN CORROSION / IRRITATION.

Causes skin irritation.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.





Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 7 / 10

SECTION 12. Ecological information. />>

12.1. Toxicity.

EDTA TETRASODIUM SALT

LC50 - for Fish. 1550 mg/l/96h

SODIUM TETRAPHENYLBORATE

EC50 - for Crustacea. 32 mg/l/48h Daphnia magna

LITHIUM HYDROXIDE

LC50 - for Fish. 109 mg/l/96h Danio rerio EC50 - for Crustacea. 33,5 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants. 41,62 mg/l/72h Pseudokirchneriella subcapitata

LC10 for Fish. 90 mg/l/96h Danio rerio
Chronic NOEC for Fish. 25 mg/l Danio rerio
Chronic NOEC for Crustacea. 4 mg/l Daphnia magna

12.2. Persistence and degradability.

EDTA TETRASODIUM SALT

Solubility in water. > 10000 mg/l

LITHIUM HYDROXIDE

Solubility in water. > 10000 mg/l

12.3. Bioaccumulative potential.

SODIUM TETRAPHENYLBORATE

Partition coefficient: n-octanol/water. 6,28 Log Kow

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

LITHIUM HYDROXIDE

Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted. Neutralisation possible in waste water treatment plants.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.



Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 8 / 10

SECTION 14. Transport information. .../>>

14	3	Transi	nort	hazard	classi	(29)
ı÷.	J.	I I alio	JUL	iiazai u	Classi	US).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

WGK 2: Hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2

©EPY 9.2.8 - SDS 1003

ΕN





Hanna Instruments S.R.L.

HI3895K-0 - Potassium Reagent

Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 9 / 10

SECTION 16. Other information. .../>>

H301 Toxic if swallowed.H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.



Revision nr.1 Dated 12/12/2016 Printed on 14/12/2016 Page n. 10 / 10

ΕN

SECTION 16. Other information. .../>>

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01/02/03/04/09/10/11/12/14/15/16.