

## **Airone X Standard School Range Ducted Fume Cupboards**



### Airone 1000X **Classroom & small prep room unit**

#### Standard specification:

- 1000mm wide (760mm deep x 2200mm high)
- Polypropylene worktop with vulcathene drip cup
- Remote water service
- Remote gas services
- Single electric socket
- Plain stand

#### **Options:**

- 900mm vented storage cabinet •
- Upgrade to double electric socket •
- Fan & inverter •

Tested by CLEAPSS

for use in schools

## Airone 1200X: Prep room unit

#### Standard specification:

- 1200mm wide (760mm deep x 2200mm high) •
- Polypropylene worktop with sink •
- Remote water service •
- Remote gas services •
- Double electric socket •
- Plain stand •

#### **Options:**

- 1100mm vented storage cabinet •
- Fan & inverter •



Tested by CLEAPSS

for use in schools

Unit shown: Airone 1200X with optional storage cabinet

# **Technical Specification**

	LOW AIRFLOW ALARM SO MARKAN MA	Control Sys	stem	Cor	
		Low airflow alarm		Epox	
		Alarm mute		Safe	
		Alarm status		Solic	
		Light on/off		Cou	
		Constant airflow monitoring		Poly	
	Mains on/off		on/off	Prof	
				Staiı	
Specification					
	Average Inflow Optimum:		0.45 m/s		
	Min Workin	200mm high			
	Max Workir	400mm l	400mm high		
	Control Pan	230V 50	230V 50Hz 1ph		
	Air Volume		Airone X 1000 Airone X 1200		
				Other standard (s Airone X 1500	

**Duct Spigot:** (1000mm-1500mm wide units) 250mm

### Optional vented storage cupboards





A one year manufacturer's warranty is supplied with the Airone R range of cabinets. COSHH Regulation Nine stipulates that this type of equipment should be tested and calibrated at intervals of no greater than 14 months to ensure continued safe operation.

So that compliance with this mandatory requirement is achieved Safelab can provide full testing and routine servicing of fume cupboards which is the key to sustained safety, reliability and economy. L54I ISS 03




#### Construction

- Epoxy coated mild steel carcass
- Safety glass side panels
- Solid grade laminate baffles
- Counterweighted front sliding sash
- Polypropylene spillage tray
- Profiled aluminium aerofoils
- Stainless steel cill

#### 1ph

- 550m<sup>3</sup>/hr 00 680m<sup>3</sup>/hr 00
- rd (size) cupboards: 870m<sup>3</sup>/hr 1060m<sup>3</sup>/hr Airone X 1800



**Dimension Drawing**