## Premium Rubber Edge

The Rubber Ramp Edge Tiles are available in 20mm, 30mm & 40mm thicknesses and provide a safe transition to lower floor levels. Floor adhesive is required to fix the ramp tiles in place.



lm Length



3-4mm granules



## **Technical Specifications**

Tile Size	L 100cm x W 25cm x D 20/30/40mm	
Tile Colour	Black	
Tile Weight	20mm 3.5kg / 30mm 45kg / 40mm 5.5kg	
Base layer	3-4mm granules	
Surface Layer	Surface layer fine granules with 15% EPDM black fleck	
Floor Hardness	is 55+/-5 ShA	
Installation	Floor adhesive is required to fix the ramp tiles in place.	
Resistance to chemicals	Good resistance to acids, alkalis and salts. Contact with oils and hydrocarbons is not advisable and will damage the floor tiles.	
Tools Required for Fitting	Stanley knife and Rubber hammer	
Cleaning	Vacuum on general setting, then lightly mop with a micro fibre mop and water mixed with a ph neutral cleaner. Do not flood the floor with water.	

## **Key Features**

Easy Cleaning and bacteria-resistant	•
Provides a safe transition to lower floor levels	•
Improves traction, offers excellent shock absorption and allows for quicker acceleration	•
Absorption of noise	•

