



# Tube Wall Bracket

## User Guide

---

This guide has been written to help you get the most from your Tube Wall Bracket. Please ensure that you read this fully as it contains important information on setting up your wall bracket. Failure to follow this advice may result in damage to the Wall Bracket and invalidate your warranty.

**Keep this guide in a safe place for future reference.**



# Unpacking

---

1. Tube Wall Brackets are shipped in specialist packaging, designed to protect the tube from damage during transport.
2. Ensure that the packaging is carefully removed from around the bracket. Keep the packaging in case the tube needs to be returned.
3. Take care when handling the wall bracket.
4. The appropriate screws for adjusting the length of the wall bracket will be found taped to the plastic bracket.
5. Do not remove the protective film from the bracket until the unit is set up to your satisfaction.
6. If you find any damage when you unpack you should report it within **7 days** to your supplier.

## Potential risks & warnings



---

1. Read and understand all these instructions before using the Tube Wall Bracket
2. Do not operate the wall bracket if the unit has been dropped or damaged.
3. Ensure you have the correct fixings for the solid wall readily available before installation.

# Setting up

---

1. The wall bracket must be attached to a solid wall using fixings appropriate to the construction of the solid wall.
2. Your wall bracket comes in two separate plastics parts. The bigger piece is lapped on top of the smaller angled piece to create a sliding piece.
3. With the provided screw, washer and nut these need to be used to attach the two plastic pieces together. In order of screw, washer, washer and then the nut.
4. Do not fully tighten the nut at this point as you may need to adjust the length of the wall bracket from your wall.
5. Ensure your tube is stood in the correct position of where you would like to install it.
6. Place the lid of the wall bracket on top of the tube and slide the wall bracket from the wall. Mark where the two slots are onto the wall.
7. Next you will need to use the correct fixing for the solid wall to complete the installation. Then the nut can be tightened on top of the slider part of the wall bracket.
8. In the unlikely event of the bracket not working fully, please contact your supplier within **7 days** of receiving.



This Wall Bracket is supplied by:



Manufactured by:

Apollo Creative  
Knaresborough Technology Park  
Manse Lane  
Knaresborough  
North Yorkshire  
HG5 8LF

**T:** 01423 798232

**F:** 01423 798239

**E:** [sales@apollocreative.co.uk](mailto:sales@apollocreative.co.uk)

**W:** [www.apollocreative.co.uk](http://www.apollocreative.co.uk)

